

NEOSTAR


Draft

2P+48w Dual-Glass mono-facial
485W-500W




Technical Features:

- Partial Shading Optimisation
- Better Temperature Coefficient
- High Temperature Restriction
- Micro-crack Resistance
- Higher Power
- Lower BOS
- More Aesthetic Values
- Zero gap Technology



red dot winner 2023

Warranty partner



Product
Warranty
Extendable to 25years*



Performance
Warranty

IEC61215/IEC61730
IEC61701/IEC62716

ISO9001:ISO Quality Management System
ISO14001:ISO Environmental Management System
ISO14064:Greenhouse Gas Verification Statement
ISO45001:ISO Occupational Health and Safety Management System

Neostar 2P+48w

AIKO-A-GRH48Dw

500W

Output

25.0%

Efficiency



$\leq 1\%$

First-year Degradation

≤0.35%

Annual Degradation from Year 2-30

30-year Linear Performance Warranty



Electrical Characteristics (STC: AM1.5 1000W/m² 25°C NOCT: AM1.5 800W/m² 20°C 1m/s)

Power Tolerance:0~ + 3%

Module Type	AIKO-A485-GRH48Dw		AIKO-A490-GRH48Dw		AIKO-A495-GRH48Dw		AIKO-A500-GRH48Dw	
Test Conditions	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
P _{max} [W]	485	373	490	377	495	381	500	385
V _{oc} [V]	35.57	33.44	35.72	33.58	35.86	33.71	36.04	33.90
V _{mp} [V]	30.27	28.42	30.42	28.56	30.56	28.69	30.71	28.84
I _{sc} [A]	16.71	13.42	16.79	13.49	16.90	13.58	16.98	13.65
I _{mp} [A]	16.02	13.13	16.11	13.20	16.20	13.28	16.28	13.36
Module Efficiency	24.3%		24.5%		24.8%		25.0%	

Product Specification

Cell Type	N-Type ABC
Front Cover	2.0mm coated semi tempered glass
Rear Cover	2.0mm semi tempered glass
Frame	Black anodized aluminum
Cable	4mm²(IEC) 12AWG(UL) ±1200mm
No. of Cells	96(6*16)
Junction Box	IP68, 3 bypass diodes
Connector	Original MC4-EVO2A
Weight	24.2kg±3%
Dimension	1762*1134*30mm
Package Detail	37pcs per pallet / 222pcs per 20'GP / 962pcs per 40'HC

Temperature Ratings (STC)

Temperature Coefficient of I_{sc}	+ 0.05%/ °C
Temperature Coefficient of V_{oc}	- 0.22%/ °C
Temperature Coefficient of P_{max}	- 0.26%/ °C
NOCT(Nominal Operating Cell Temperature)	45°C (±2°C)

Installation Guide

Operation Temperature	-40°C - +70°C
Maximum Series Fuse Rating	30A
Protection Class	Class II
Maximum System Voltage	DC1500V
Maximum Static Loading	Front 5400Pa Back 2400Pa
Hail Test	25 mm diameter hail at 23 m/s
Fire Rating	IEC Class A



www.aikosolar.com
marketing@aikosolar.com

*AIKO reserves right to update the specification without notice
*Optional Munich Re coverage is available upon request
202607 V4.2 EN