SG125CX-P2

Multi-MPPT String Inverter for 1000 Vdc System

HIGH YIELD

- 12 MPPTs with max. efficiency 98.5%
- DC 15A current input, compatible with over 500W+ PV module
- Dynamic shading optimization mode

SMART O&M

- Key component diagnosis and protection
- Smart IV Curve Diagnosis
- Grid fault record function, easy for remote O&M

LOWER INVESTMENT

- Compatible max. 240mm2 Al AC cables
- Drawer-style cable sealing plate support AC cable pre-assembly

PROVEN SAFETY

- IP66 protection and C5 Anti-corrosion
- DC Type I+II SPD, AC Type II SPD
- Support AFCI 2.0 function

CIRCUIT DIAGRAM



EFFICIENCY CURVE



© 2024 Sungrow Power Supply Co., Ltd. All rights reserved. Subject to change without notice. Version 6

SUNGROW
Clean power for all

Type designation	SG125CX-P2
Input (DC)	
Recommended max. PV input power	175 kW
Max. PV input voltage *	1100 V
Min. PV input voltage / Startup input voltage	180 V / 200 V
Rated PV input voltage	600 V
MPPT voltage range **	180 V – 1000 V
No. of independent MPP inputs	12
No. of PV strings per MPPT	2
Max. PV input current	360 A (30 A * 12)
Max. DC short-circuit current	480 A (40 A * 12)
Max. current for DC connector	30 A
Output (AC)	
Rated AC output power	125 kW
Max. AC output apparent power	125 kVA
Max. AC output current	181.1 A
Rated AC output current(at 230V)	181.1 A
Rated AC voltage	3 / N / PE, 220 V / 380 V; 230 V / 400 V
AC voltage range	320 V – 480 V
Rated grid frequency	50 Hz / 60 Hz
Grid frequency range	45 Hz – 55 Hz / 55 Hz – 65 Hz
Harmonic (THD)	< 3 % (at rated power)
Power factor at rated power / Adjustable power factor	> 0.99 / 0.8 leading – 0.8 lagging
Feed-in phases / AC connection	3 / 3-N-PE
Efficiency	
Max. efficiency / European efficiency	98.5% / 98.3%
Protection & function	
Grid monitoring	Yes
DC reverse polarity protection	Yes
AC short-circuit protection	Yes
Leakage current protection	Yes
Surge protection	DC Type I + II / AC Type II
Ground fault monitoring	Yes
DC switch	Yes
PV string current monitoring	Yes
Arc fault circuit interrupter (AFCI)	Yes
PID recovery function	Yes
Optimizer compatibility ***	Optional
RSD compatibility ***	Optional
General data	
Dimensions (W * H * D)	1020 mm * 795 mm * 360 mm
Weight	≤ 93 kg
Mounting method	Wall-mounting bracket
Topology	Transformerless
Degree of protection	IP66
Night power consumption	< 5 W
Corrosion	C5
Operating ambient temperature range	-30 ℃ - 60 ℃
Allowable relative humidity range (non-condensing)	0 % - 100 %
Cooling method	Smart forced air cooling
Max. operating altitude	4000 m
Display	LED, Bluetooth+APP
Communication	RS485 / WLAN (optional) / Ethernet (optional)
DC connection type	EVO2 (Max. 6 mm²)
AC connection type	OT / DT terminal (Max. 240 mm²)
AC cable specification	Outside diameter 30 mm - 60 mm
Grid compliance	IEC 62109-1, EN/IEC 61000-6-1/2/3/4, IEC 61727, IEC 62116, EN 50549-1/2, UTE C15-712-1, VDE V 0126-1-1, VDE-AR-N 4105:2018, VFR 2019, NC RfG, G99, UNE 217002, NTS, CEI 0-21 2019,CEI0-16 2019, NRS-097-2-1, IEC 63027
Grid support	Q at night function, LVRT, HVRT, active & reactive power control and power ramp rate controlramp rate control

* Input voltage exceeding the MPPT operating voltage range triggers inverter protection
** Please refer to the user manual for the full load MPPT voltage range
*** For optimizer & RSD compatibility, please consult Sungrow before placing an order

© 2024 Sungrow Power Supply Co., Ltd. All rights reserved. Subject to change without notice. Version 6