YINGLI SOLAR

panda 3.0 Mini 1

445W

MAXIMUM MODULE EFFICIENCY

22.8%

POSITIVE POWER TOLERANCE

0~+5w

N

N-type TOPCon Bifacial Module

IMPROVED POWER
NEVER SETTLE FOR LESS

- Backside Yield
- Wide Applications
- Superior Yield
- Outstanding Bifaciality
- Excellent Durability

30 YEAR POWER WARRANTY

12 YEAR PRODUCT WARRANTY

Yingli Solar Website

QUALIFICATIONS & CERTIFICATES

IEC 61215, IEC 61730, CE
ISO 9001: Quality management systems
ISO 14001: Environmental management systems
IEC 62941: Quality system for PV module manufacturing
ISO 45001: Occupational health and safety management systems

Warranty partner
Munich RE



1.00% the 1st year power degradation
0.40% annual power degradation

panda 3.0 Mini 1

YINGLI SOLAR

BACK VIEW
(units:mm)





DETAIL I



SECTION A-A



SECTION B-B



Warning: Read the Installation and User Manual in its entirety before handling, installing and operating Yingli Solar modules.

Electrical Parameters at Standard Test Conditions (STC)

Module type	YLxxxCF54 e/2 (xxx=Pmax)					
Power output*-Pmax (W)	420	425	430	435	440	445
Power output tolerances–ΔPmax (W)	0 / + 5					
Module efficiency-η_m (%)	21.5	21.8	22.0	22.3	22.5	22.8
Voltage at Pmax - Vmpp (V)	31.51	31.70	31.89	32.08	32.27	32.46
Current at Pmax-Impp (A)	13.33	13.41	13.49	13.56	13.64	13.71
Open-circuit voltage*-Voc (V)	38.13	38.32	38.51	38.69	38.87	39.05
Short-circuit current*-Isc (A)	14.03	14.09	14.15	14.22	14.29	14.36

STC: 1000 W·m^{-2} irradiance, 25℃ cell temperature, AM 1.5. *Measruing tolerance: ±3%.

Electrical Parameters at Nominal Operating Cell Temperature (NOCT)

Power output-Pmax (W)	319	323	327	331	335	338
Voltage at Pmax - Vmpp (V)	30.06	30.24	30.42	30.60	30.78	30.97
Current at Pmax-Impp (A)	10.63	10.69	10.76	10.81	10.87	10.93
Open-circuit voltage-Voc (V)	36.21	36.39	36.57	36.74	36.91	37.08
Short-circuit current-Isc (A)	11.30	11.35	11.40	11.46	11.51	11.57

NOCT: open-circuit module operation temperature at 800 W·m^{-2} irradiance, 20℃ ambient temperature, 1 m · s^{-1} wind speed.

Bifacial Electrical Parameters at Standard Test Conditions(BNPI)

Power output-Pmax (W)	465	471	477	482	488	493
Voltage at Pmax - Vmpp (V)	31.51	31.70	31.89	32.08	32.27	32.46
Current at Pmax-Impp (A)	14.77	14.86	14.95	15.02	15.11	15.19
Open-circuit voltage-Voc (V)	38.13	38.32	38.51	38.69	38.87	39.05
Short-circuit current-Isc (A)	15.55	15.61	15.68	15.76	15.83	15.91

BNPI: 1000W·m^{-2} on the front side and 135 W·m^{-2} on the back side , 25℃ cell temperature, AM 1.5.
Bifaciality coefficient is 80% ± 5%.

Thermal Characteristics

Nominal operating cell temperature–NOCT(℃)	42±2
Temperature coefficient of Pmax–γ(% / ℃)	– 0.29
Temperature coefficient of Voc–β(% / ℃)	– 0.24
Temperature coefficient of Isc–α(% / ℃)	0.042

Packaging Specifications

Number of modules per pallet	36
Number of pallets per 40' container	26
Packaging box dimensions (L / W / H)	1740 mm / 1110 mm / 1245 mm
Box weight	778 kg

Operating Conditions

Max. system voltage	1500 VDC
Max. series fuse rating*	30 A
Operating temperature range	– 40℃~ 85℃
Max. static load, front (e.g., snow)	5400 Pa
Max. static load, back (e.g., wind)	2400 Pa
Max. hailstone impact (diameter / velocity)	25 mm / 23 m·s^{-1}

*Do not connect fuse in combiner box with two or more strings in parallel connection.

General Characteristics

Dimensions (L / W / H)	1722 mm / 1134 mm / 30 mm
Weight	20.6 kg

Construction Materials

Cell (material / quantity)	n-type monocrystalline silicon / 6 x 18
Glass (thickness)	1.6 mm / 1.6 mm
Frame (material)	anodized aluminum alloy
Junction box (type / protection degree)	3 bypass diodes / ≥ IP68
Cable (length / cross-sectional area)	± 1200 mm / 4 mm^2

- Due to continuous innovation, research and product improvement, the specifications in this product information sheet are subject to change without prior notice. The specifications may deviate slightly and are not guaranteed.
- The data do not refer to a single module and they are not part of the offer, they only serve for comparison to different module types.

Yingli Solar Website

©Yingli Energy Development Co., Ltd.
service@yingli.com Tel: +86–312–8922216