

AXPERT ULTRA TWIN

150A
DUAL MPPT

PV10000 PV12000

AXPERT ULTRA TWIN 8KW & 11KW
AXPERT ULTRA TWIN - HYBRID



KEY SALIENT FEATURES

- ✓ INTRODUCING ORIGINAL DESIGN AND ENGINEERING IN TAIWAN
- ✓ TWO INDEPENDENT AC POWER SOURCES CONNECTED AND SWITCHED AUTOMATICALLY
- ✓ MAXIMUM CHARGING CURRENT 150A
- ✓ SUPPORTS USB ON-THE-GO FUNCTION
- ✓ RESERVED COMMUNICATION PORT FOR BMS (RS485, CAN-BUS OR RS232)
- ✓ BUILT-IN FEED-IN GRID FUNCTION
- ✓ BUILT-IN 2.8" COLORED LCD WITH SLIDE OPERATION
- ✓ BUILT-IN POWER STATUS LIGHTING INDICATORS
- ✓ SUPPORT EXTERNAL BTS (BATTERY TEMPERATURE SENSOR) DETECTION
- ✓ BUILT-IN WIFI WITH APP FOR REMOTE MONITORING AND OTA FIRMWARE UPGRADE
- ✓ ADAPTABLE TO MAIN VOLTAGE / GENERATOR POWER
- ✓ CONFORMAL COATING TO PREVENT FROM DUST AND HUMIDITY
- ✓ DUAL AC OUTPUTS FOR SMART LOAD MANAGEMENT
- ✓ COMPATIBLE WITH ALL KINDS OF LITHIUM BATTERIES
- ✓ OVERLOAD & SHORT CIRCUIT PROTECTION
- ✓ SUPPORT OPTIONAL GFCI, RAPID SHUTDOWN, AFCI DETECTION
- ✓ BUILT-IN COMMUNICATION PORT FOR BMS
- ✓ BATTERY EQUALIZATION FUNCTION TO OPTIMIZE BATTERY PERFORMANCE AND EXTEND LIFECYCLE
- ✓ PARALLEL OPERATION WITH 6 UNITS

ORIGINAL

DESIGN & ENGINEERING IN
TAIWAN



BUILT-IN
WIFI MONITORING



(iOS)



(Android)



AVAILABLE ON



ZIEWNIC
Solar Energy

MODEL	AXPERT Ultra - PV10000	AXPERT Ultra - PV12000
Rated Power	8000VA/8000W	11000VA/11000W
Parallel Capability	YES, 6 units	
AC INPUT		
Voltage	230 VAC	
Selectable Voltage Range	170 - 280 VAC (For Personal Computer)	
Frequency Range	90 - 280 VAC (For Home Appliances)	
AC OUTPUT		
AC Voltage Regulation(Batt. Mode)	230VAC ± 5%	
Surge Power	16000VA	22000VA
Efficiency (Peak)	93%	
Transfer Time	10ms (Personal Computer) ; 20 ms (For Home Appliances)	
Waveform	Pure Sine Wave	
BATTERY		
Battery Voltage	48 VDC	
Floating Charge Voltage	54VDC	
Overcharge Protection	63VDC	
SOLAR CHARGER & AC CHARGER		
Solar Charger Type	MPPT	
Maximum PV Array Power	10000 (5000W X 2)	12000W (6000W X 2)
MPPT Range @ Operation Voltage	90 ~ 450 VDC	
Maximum PV Array Open Circuit Voltage	500 VDC	
Maximum PV Input Current	27A x 2 (MAX 40A)	
Maximum Solar Charge Current	150A	150A
Maximum AC Charge Current	120A	150A
Maximum Charge Current	150A	150A
PHYSICAL		
Dimension D x W x H (mm)	145 x 438 x 553.6	
Net Weight (Kgs)	18.4	
Communication Interface	USB/RS232/RS484/WiFi/Dry-Contact/BTS Support optional GFCI, Rapid Shutdown, AFCI detection	
External Current Sensor Port	Yes, built-in current transformer sensor	
PHYSICAL		
Humidity	5% to 95% Relative Humidity (Non-condensing)	
Operating Temperature	-10°C to 50°C	
Storage Temperature	-15°C to 60°C	
STANDARD		
Compliance Safety	CE	

Note: Product specifications are subject to change without further notice



MAX PV INPUT
10000 / 12000



MAX CHARGING
CURRENT 150A



MAX PV VOLTAGE
500VDC



DUAL AC
OUTPUT



MPPT RANGE
60~450VDC



WORK WITH &
WITHOUT BATTERIES



IP-21
PROTECTION



COLORLED LCD WITH
SLIDER OPERATION



COMMUNICATION
PORT



PURE SINE WAVE
INVERTER



POWER
FACTOR 1.0



BUILT-IN
WI-FI



BATTERY
MANAGEMENT
SYSTEM (BMS)



NET METERING
(FEED INTO GRID)



ZERO
EXPORT



SMART & SAFE



ANTI DUST
PROTECTION



SHORT CIRCUIT
PROTECTION



PARALLEL UP
TO 6 UNITS



USB PORT



DUAL AC
INPUT



SMART LOAD
MANAGEMENT



DUAL MPPT
HIGH PV CAPACITY



POWER STATUS
LED LIGHTING
INDICATORS